

DECLARATION OF PERFORMANCE

CONF-DOP_LSA-L-01-22

No. H-19-845-1/5-E

1.	Unique identification code of the product-type	HALFEN LSA-L Cavity wall tie		
2.	Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4)	HALFEN LSA-L 235/4 see label on product packaging		
3.	Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:			
	Generic type and use	Asymmetric cavity wall tie for horizontal connection of a cavity wall		
	Product size covered (anchor channels and corresponding screws)	235/4		
	For use in	Lightweight perforated brick		
	Anchor material / Screw material and intended use	HALFEN LSA-L: <ul style="list-style-type: none"> Stainless steel 1.4401 / 1.4404 / 1.4571 acc. to DIN EN 10088-2 for medium corrosion exposure Nylon anchor 		
	Loading	Static and quasi static loading		
4.	Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5)	Leviat GmbH, Liebigstraße 14, 40764 Langenfeld, Deutschland		
5.	Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2)	-		
6.	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 3 acc. to EN 845-1		
7.	In case of the declaration of performance concerning a construction product covered by a harmonised standard	The notified testing laboratory MPA Bau Hannover, Nienburger Str. 3, Hannover (0764) performed the initial testing under System 3 and issued a test report No. 132140.		
8.	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	-		
9.	Declared performance			
	Type	Essential Characteristics	Performance	Harmonized Technical Specification
	LSA-L	Max tension load with lightweight perforated bricks	1050 N	DIN EN 845-1:2008 / E DIN EN 845-1: 2012-10
		Max compression load up to 160 mm cavity	660 N	
		Anchorage length in faced brickwork	min. 50 mm	
		Punching protection	30 mm	
Anchorage in supporting lightweight perforated brick wall		Plastic anchor		

DECLARATION OF PERFORMANCE

CONF-DOP_LSA-L-01-22

No. H-19-845-1/5-E

LSA-L	Anchorage in faced brickwork	Bent end	DIN EN 845-1:2008 / E DIN EN 845-1: 2012-10
	Water-repelling function	No resistance	
	Durability	Material reference 1	
	Dangerous substances	NDP	
Where pursuant to Article 37 or 38 in the Specific Technical Documentation has been used, the requirements with which the product complies:		-	
10.	The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.		
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.			

Langenfeld, 02.01.2022

Signed for and on behalf of the manufacturer by



Chris Oberli
(Managing Director | Europe Central)



Dr. Ing. Dirk Albartus
(Prokurist)